



Reclaimed teak from Southeast Asia with an authentic weathered patina from decades of tropical seasoning and use. This is an incredible product, beautiful for floors, feature walls and other standard or custom paneling applications.

Allowed Application Areas

INTERIOR			EXTERIOR	
Floors	Walls	Ceilings	Siding	Decking
Yes	Yes	Yes	No	No

Approved Installation Methods

- Nail/Staple/Cleat
- Glue & Nail (100% moisture-curing polyurethane or silane-modified polymer - AXIOS or MS-Polymer)

Acclimation

The planks should be stored in a clean, dry, controlled environment between 60°F (16°C) and 80°F (27°C) and 35% to 55% RH, until the wood has achieved equilibrium moisture content. See the [TerraMai Flooring/Paneling Acclimation Instructions](#) for further information.

Options

Class A Flame Retardant

Profile

T&G, Square Edge, End Matched



TERRAMAI

TEAK
ENGINEERED
FLOORING & PANELING

Wood is a natural material. Variation in color and grain pattern are to be expected.
For more information or to place an order, please contact your [local TerraMai Rep.](#)



SKU	397
Finish Option	Poly
Face Width	5-1/8" (130mm)



SKU	398
Finish Option	Clear Oil
Face Width	5-1/8" (130mm)



SKU	547
Finish Option	Kukui
Face Width	5-1/8" (130mm)

Species	<i>Tectona grandis</i>
Source	Reclaimed from vintage structures in Southeast Asia.
Character	Prefilled nail and other holes, oxide stains, prefilled surface seasoning checks and occasional sound tight knots
Finish*	Zero-VOC clear oil, low-VOC polyurethane, or unfinished
Thickness	9/16" (14mm)
Widths	5-1/8" (130mm)
Lengths	70-7/8" - 82-5/8" (1,800 - 2,099mm)
Construction	Engineered
Wear Layer	5/32" (4mm)
# of Backer Plies	7
Filler	Sawdust & Epoxy
Janka/Hardness	1,070 lbs (4.8 kN)
Moisture Content	6%-9%
Knots	Prefilled surface seasoning checks and occasional sound tight knots, oxide stains
Nail Holes	Prefilled nail and other holes
Saw Marks	No
Grain	Mixed Grain
Density	41 lbs/ft ³ (657 kg/m ³)
Packaging	Boxed <ul style="list-style-type: none"> • 17.63 square feet per box

*Custom finishes available.

For more information on installation guidelines, please visit TerraMai.com and see [Flooring Installation Instructions](#) or [Paneling Installation Instructions](#).

CERTIFICATIONS



FSC Mix 100% - FSC-C021798



VOC Reduction - Feature 4
Toxic Material Reduction - Feature 25

CONTRIBUTES TO TO LEED® V4

EQ Credit: Low-Emitting Materials - Flooring
(1-3 Points)