

TerraMai's MC Walnut Herringbone provides timeless subdued elegance for any type of space. Reclaimed American Black Walnut with a natural oil or uv cured polyurethane finish.

Allowed Application Areas

INTERIOR			EXTERIOR	
Floors	Walls	Ceilings	Siding	Decking
Yes	Yes	Yes	No	No

Approved Installation Methods

- Nail/Staple/Cleat
- Glue & Nail (100% moisture-curing polyurethane or silane-modified polymer - AXIOS or MS-Polymer)

Acclimation

The planks should be stored in a clean, dry, controlled environment between 60°F (16°C) and 80°F (27°C) and 35% to 55% RH, until the wood has achieved equilibrium moisture content. See the [TerraMai Flooring/Paneling Acclimation Instructions](#) for further information.

Options

Class A Flame Retardant

Profile

T&G, Square Edge, End Matched




TERRAMAI

WALNUT MC HERRINGBONE
ENGINEERED
FLOORING & PANELING

Wood is a natural material. Variation in color and grain pattern are to be expected.
For more information or to place an order, please contact your [local TerraMai Rep.](#)



SKU	833
Finish Option	Clear Oil
Face Width	3-1/8" (79mm)



SKU	842
Finish Option	Oyster Wash
Face Width	3-1/8" (79mm)

SKU	834
Finish Option	Poly
Face Width	3-1/8" (79mm)

Species	<i>Juglans nigra</i>
Source	Reclaimed American Black Walnut from post-industrial manufacturing in the U.S.
Character	Typical walnut tones ranging from lighter to darker material. These color tones may blend over time as exposure to light softens the color range.
Finish*	Zero-VOC clear oil, low-VOC polyurethane, or unfinished
Thickness	9/16" (14mm)
Width	3-1/8" (79mm)
Length	16" (406mm)
Construction	Engineered
Wear Layer	1/8" (3mm)
# of Backer Plies	3
Filler	N/A
Janka/Hardness	1,010 lbs (4.5 kN)
Moisture Content	6%-9%
Knots	Very occasional small and sound tight knots
Nail Holes	No
Saw Marks	No
Grain	Quarter-Sawn Vertical Grain
Density	38 lbs/ft ³ (609 kg/m ³)
Packaging	Boxed

*Custom finishes available.

For more information on installation guidelines, please visit [TerraMai.com](https://www.terramai.com) and see [Flooring Installation Instructions](#) or [Paneling Installation Instructions](#).

CERTIFICATIONS



FSC Mix 76% - FSC-C021798



FloorScore® -SCS-FS-03865



VOC Reduction - Feature 4
Toxic Material Reduction - Feature 25

CONTRIBUTES TO LEED® V4

EQ Credit: Low-Emitting Materials - Flooring
(1-3 Points)